

ROLAND GX-24

CUTTER	BLADE	FORCE	OFFSET	SPEED
Thermo-Film®	45°/60°	120-160g 140-170g	.25 .50	50cm/s
Thermo-Grip®	45°/60°	140-170g 120-170g	.25 .50	50cm/s
Thermo-Flock®	Flock Blade RBFL	170-220g	.50	50cm/s
GORILLA-GRIP®II	45°/60°	100-150g 80-100g	.25 .30	50cm/s
Econoprint	45°/60°	200-240g 250g	.25 .425	50cm/s
Reflective	45°/60°	100-160g 140-170g	.25 .30	50cm/s
Glitter	45°/60°	120-150g 120-150g	.25	50cm/s
Neon	45°/60°	160-200g 180-220g	.15 .50	50cm/s
Fashion-FILM™	45°/60°	80-120g 70-130g	.25 .50	50cm/s
Fashion-REFLECT™	45°/60°	90-130g 80-120g	.25 .60	50cm/s
Pressure Sensitive Sign Vinyl	45°/60°	140-180g 130-150g	.25 .425	50cm/s

The recommendations given are guidelines only, based on a new, unused blade. Always perform a test cut before production to determine the settings for your cutter.

All technical information and recommendations are based on tests we believe to be reliable. However, we cannot guarantee performance for conditions not under manufacturer's control. Before using, please determine the suitability of product for its intended use. The user assumes all risk and liability whatsoever in connection with the use of this product. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective by manufacturer.

CAD-CUT, CAD-LAB, Pressure Sensitive Poly-TWILL, & Hotronix are trademarks & ® trademarks of GroupeSTAHL™ with one or more patents or patents pending.
 © Stahls' International™ 2009 - All International Rights Reserved