

APPLICATION INSTRUCTIONS FOR
Materials by the yard
Available width: 40" (100 cm)



t (001) 586.772.5551 f (001) 586.772.6237
e info@stahlsinternational.com w StahlsInternational.com

Glitter Flake™

Glitter Flake™ has a slightly raised texture that is pleasant to the touch. Choose from over a dozen different sparkling, glittery colors that will enhance any design whether it be used for fashion, team or cheer wear. Not mounted on a carrier (115 micron [+/- 10%]).

Recommended Fabrics

- 100% cotton
- 100% polyester

Due to the combination of fabrics, weaves, coatings and dyes used in the textile industry, Stahls' recommends and provides samples of our materials and medias for testing.



PREHEAT LOWER PLATEN

Before application, Stahls' recommends lowering the upper platen for 60 seconds. This helps the adhesive to melt more evenly during application.

Accessories Required

Kraft Paper or Reusable Cover Sheet



PREHEAT & POSITION

It is pertinent to preheat garment for 5-10 seconds, prior to application.

Position design adhesive side down on garment (reads left to right). Cover with Kraft Paper or Reusable Cover Sheet before pressing.

Care Instructions

Turn garment inside out. Machine wash warm or hot using mild detergent. Do not use bleach. Dry at a normal dryer setting on household machines. Do not dry clean.



HEAT APPLY

Temperature: 320°F; 160°C
Time: 10-15 seconds
Pressure: firm (#6-7 on Hotronix®)

Multi-Color Designs

Not recommended for multi-layer applications.

Storage

Store in a cool, dry area. Avoid direct heat, sunlight and humidity.

All technical information and recommendations are based on tests we believe to be reliable. However, we cannot guarantee performance for conditions not under manufacturer's control. Before using, please determine the suitability of product for its intended use. The user assumes all risk and liability whatsoever in connection with the use of this product. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective by manufacturer.

CAD-CUT, Pressure Sensitive Poly-TWILL, & Hotronix are trademarks & ® trademarks of GroupeSTAHL™ with one or more patents or patents pending.
© Stahls' International™ 2013 - All International Rights Reserved